

Rennaker, Joanne (DEQ)

From: Matta, Samir <SFMatta@lan-inc.com>
Sent: Tuesday, October 27, 2015 4:12 PM
To: Prysby, Mike (DEQ)
Cc: Brent Wright (bwright@cityofflint.com); Mike Glasgow (MGlasgow@Cityofflint.com)
Subject: FW: Flint WTP PH2 SEG4 - Corrosion Control
Attachments: LMI Series C Pumps.pdf; NSFPhosAcidSpecs.pdf; PhosAcidSafetyDataSheet.pdf; Flint Phosphate Calculations - Revision 4.pdf

Hi Mike,

I have included the updated calculations, Proposed Pump Cut Sheet as well as the MSDS and the fact sheet for the chemical to be used.

Please let me know if this satisfy your needs to issue the permit.

Thanks,

Samir F. Matta, PE
 Team Leader



**Lockwood, Andrews
& Newnam, Inc.**
 A LEO A DALY COMPANY

1311 South Linden Road, Suite B • Flint, MI 48532
 2121 University Park Dr, Suite 100 • Okemos, MI 48864-6901
 D 517.819.2367 C 517.819.2367
www.lan-inc.com • sfmatta@lan-inc.com

CONFIDENTIALITY AND PRIVILEGE NOTICE: This email communication, including any and all attachments, (collectively, this "Communication"), is intended solely for the person(s) to whom it is addressed. This Communication may contain information that is privileged, confidential and/or proprietary. Any unauthorized use, disclosure or copying of this Communication is strictly prohibited. If you have received this Communication in error, please contact the sender immediately and destroy any and all copies of this Communication.

Home


Sub


[COMPANY](#) [PRODUCTS](#) [MARKETS](#) [DISTRIBUTOR LOCATOR](#) [RESOURCES](#) [CONTACT US](#)
[LMI](#) [PRODUCTS](#) [Metering Pumps](#) [Series C Chemical Metering Pumps](#)

Series C Chemical Metering Pumps

Series C Chemical Metering Pumps

Series C Chemical Metering Pumps have been an industry standard for over 20 years. Designed for Municipal/Industrial applications, the familiar yellow and black pumps have a rugged, totally enclosed, chemically resistant housing for protection in the harshest environments. Encapsulated electronics and a rigid housing and stroke bracket ensure years of precise, repeatable performance.



High Speed Stroke Range

[Request a Quote](#)

[Features Tab](#)
[Information Tab](#)
[Options Tab](#)

Adjustable stroke frequency and the flexibility of up to 1000:1 turndown ratio
 Manually adjustable stroke length provides accurate pump output adjustment
 NEMA 4X / IP65 enclosures for protection against corrosive environments
 Time tested electronics for reliable, repeatable performance
 Totally encapsulated electronics for protection against moisture and corrosive conditions
 Inputs for low level switch available on certain models
 Models with external pacing for flow proportional applications
 Advanced control options for simplified system integration (pulse multiply/divide, 4-20 mA, remote on/off)
 *UL, *CUL, NSF 50, NSF 51, *CE Certifications

Control Codes:

1 - Dual Manual Control (speed and stroke length)

7 - Pulse Input / Dual Manual Control

8 - Pulse/Analog Input / Dual Manual Control

Output Codes with standard liquid end	
Max Capacity:	Max Pressure:
*CX0 - 1.3 GPH (4.8 l/h)	300 psi (20.7 Bar)
*CX1 - 2.5 GPH (9.5 l/h)	150 psi (10.3 Bar)
*CX2 - 4.0 GPH (15.1 l/h)	100 psi (6.9 Bar)
*CX3 - 8.0 GPH (30.3 l/h)	50 psi (3.4 Bar)
*CX4 - 20 GPH (75.7 l/h)	25 psi (1.7 Bar)
C76 - 4.0 GPH (15.1 l/h)	175 psi (12.1 Bar)
C77 - 10.0 GPH (37.8 l/h)	80 psi (5.5 Bar)
C78 - 25 GPH (95.0 l/h)	30 psi (2.07 Bar)